

		SL-D1000	SL-D1000A
Print Technology	Printing Method	Epson Micro Piezo drop-on-demand inkjet technology, High-performance print head technology designed for robust printing environments, Variable Sized Droplet Technology	
	Max. Resolution	1440 x 720 dpi	
	Minimal Droplet Size	2.5 pl	
	Print Speed Simplex - High Speed / Standard / High Quality	460 / 385 / 200 - 15 x 10 cm (6 x 4 ") prints/h	
	Print Speed Simplex - Single Print using Quick Print Mode	in 17 sec - 15 x 10 cm (6 x 4 ") prints	
Ink	Print Speed Duplex - Standard	n/a	30 - A4 prints/h
	Ink Set	6 Colours, Integrated Ink Pack System, T46K Ink Family	
	Available Colors	Black, Cyan, Light Cyan, Light Magenta, Magenta, Yellow	
	Ink volume per color	250ml	
	Ink Technology	Ultrachrome® D6r-S	
Media	Media Handling	65m Roll (simplex); manual feed (single sheet simplex, auto duplex)	65m Roll (simplex); manual feed (single sheet simplex, auto duplex); 100 A4 sheet cassette (simplex, auto duplex)
	Supported Roll Width	89mm (3.5-inch); 102mm (4-inch), 127mm (5-inch), 152mm (6-inch), 203mm (8-inch), 210mm	
	supported Sheet Size (manual feed simplex)	Width:89mm~210mm Length:148mm~1000mm	
	Supported Sheet size (cassette / duplex)	Width:89mm~210mm Length:148mm~297mm	Width:89mm~210mm Length:148mm~297mm
	Paper thickness (Roll paper)	0.22mm~0.25mm	
	Paper thickness (manual feed simplex)	0.20mm~0.50mm	
	Paper thickness (cassette / duplex)	0.20mm~0.265mm	0.20mm~0.265mm
Connectivity	Interfaces	Hi-Speed USB, 100BASE-TX/10BASE-T, IEEE802.11b/g/n (WiFi)	
	Printer Language	ESC/P-R	
	Memory	1GB	
Environmental Conditions	Temperature(Operating)	10 to 35 °C	
	Humidity(Operating)	20 to 80 % (no condensation)	
	Temperature(Storage)	Storage (before unpacking): -20°C - 60°C 1 month at 40°C, 120 hours at 60°C Storage (after	
	Humidity(Storage)	5 - 85% (no condensation)	
Dimensions WxDxH [mm³]	Printing (open Tray)	460x683x359	460x747x441
Dimensions WxDxH [mm³]	Printing (open Tray + Manual Feed cover open)	460x726x393	460x747x475
Dimensions WxDxH [mm³]	Storage / Size in cabinet	460x374x343	460x438x424
Weight [kg]		17.6kg	23.1kg
Device Security		Kensington lock connection; lockable Ink compartment(s); Password Encryption (LCD)	
Controlpanel		Color / 1.44 inch	
Electrical Specification	Voltage; Rated Current	AC 100 to 120V, 220 to 240V,50/60Hz; 1.4A	
Power Consumption	Operating / Ready / Sleep / Power off (Standby)	Approx 80W / Approx. 14W / Approx. 1.2W / Approx. 0.2W	
Acoustic Noise Level	Sound Pressure Level <db(A)>	Approx. 50dB(A) or less	
Options	Options	Duplex Feeder,Spindle; EPSON SureLab OrderController; EPSON SureLab OrderController LE	Spindle; EPSON SureLab OrderController; EPSON SureLab OrderController LE
Consumables	Consumable	Maintenance Box,Roller Assembly Kit; T46K Ink set; SureLab Pro-S Paper Glossy/Luster range; Surelab Photo Paper DS Glossy/Luster 190; Surelab Photo Paper DS Glossy/Luster 225; Surelab Photo Paper Glossy/Luster 250	
System	supported OS	OS :Windows®10; Windows®8.1; for each 32bit/64bit OS: Macintosh Mac OS X (10.9.5 or later); macOS 11x Linux	
Others	Product Lifetime	Replacement timing of lifetime management parts: 400,000 sheets printing or 5 years use	
What's in the Box	What's in the box	Printer, Spindle unit, Maintenance Box, Setup guide, CD, AC cable	Printer, Duplex Feeder (incl. 100 >=A4 Sheet cassette); Spindle unit, Maintenance Box, Setup guide, CD, AC cable

Product information is subject to change without prior notice, Status August 2021.